

# General Specifications

## Model YHC5150X FieldMate Handheld Communicator

# FieldMate™

GS 01R01A30-01EN-A

The YHC5150X FieldMate Handheld Communicator is the latest Intrinsically Safe HART® communicator from Yokogawa Corporation of America. All HART® field devices can be configured, polled, and trimmed utilizing a Windows-Embedded CE™ based system for faster processing and greater storage capacity. In addition, all options are standard, and no subscription is required. The YHC5150X is a full function, DD Direct, HART® Communicator supporting Universal, Common Practice and Device Specific commands for commissioning, configuration, and maintenance operations.

### FEATURED FUNCTIONS

- Reads manufacturers' DDs in their native format without the need for translations
- HART®-compliant modem communicates with any registered or unregistered HART® Device, including HART® 6 and 7
- Features an ergonomic, handheld design
- Enhanced 4.3" diagonal anti-glare touchscreen with color graphic display (no stylus required)
- Full QWERTY keyboard for commissioning new transmitters
- On Demand Help Menus and teachable device-specific short cuts
- More than twice the battery capacity of any handheld communicator
- Manage device information
- Integrated multi-language support

### STANDARD SPECIFICATIONS MODEL YHC5150X

#### Processor and Memory:

Microprocessor: 1 GHz  
Memory Internal Flash: 512 MB  
System Card: Up to 64 GB secure digital card (4 GB installed)  
RAM: 256 MB

#### Physical:

Weight: Approximately 2.1 lbs (.91 Kg) with battery  
Display: ¼ VGA (480 X 272 pixels) color, 4.3 (10.9 cm) transfective display with anti-glare Touch screen  
Size: 303×142×48 mm [11.9×5.6×1.9 inch]  
Keypad: 52 keys including QWERTY keys  
12 alphanumeric keys, tab key, backlight key, Power key, and 4 cursor-control (arrow) keys;  
Membrane design with tactile feedback

#### Power Supply / Charger:

Battery: Rechargeable Lithium-Ion power module  
Battery Operating Time: 10 Hours – continuous use  
20 hours – typical use, 100 hours – standby/hibernate  
Battery Charger: Input Voltage 100-240 VAC,  
50-60 Hz, Asian Adapters included US, European, and UK.

#### Connection:

Battery Cradle  
HART®: Two 4mm banana plugs  
(One common to HART®)  
USB: Supporting up to 115 kbps

#### Environmental:

Usage: +14°F (-10°C) to +122°F (+50°C)  
0% to 95% RH (non-condensing) (for +32°F ; 0° C) to +122°F (+50°C)  
Charge: +50 °F (+10 °C) to +104 °F (+40 °C)  
Storage: With Batteries -4°F (-20°C) to +131°F (+55°C)  
Without Batteries -4°F (-20°C) to +150°F (+60°C)  
Enclosure Rating: IP51  
Shock: Tested to survive a 1 meter drop onto concrete


#### Shipping Weight:

5 lbs (2.3 Kg) ; Varies by option

#### Certification:

Class I, Division 1, Groups A,B,C,D; T4 (cULus)  
II 1G Ex ia IIC T4 Ga (ATEX)  
Ex ia IIC T4 Ga (IECEX)





## YHC5150X FieldMate Handheld Communicator

YHC5150X	FieldMate Handheld Communicator
	Standard Option
	Includes: Docking Station w/ Universal Power Adapter, HART <sup>®</sup> Test Lead Kit (Standard banana plugs, Mini-grabbers, 250 Ohm resistor), Rechargeable Battery, USB Cable, FieldMate Carrying Case, Hand Strap, SD Card, and Software (CD-ROM)

Example Part Number: YHC5150X

## YHC5150X Accessories

1W-9A879	Docking Station w/ Universal Power Adapter (100 VAC to 240 VAC, 50-60 Hz)
1W-A900529-00014	HART <sup>®</sup> Test Lead Kit - Standard banana plugs, Mini-grabbers, 250 Ohm resistor
1W-A36821	Resistor - Std size 250 ohm shunt (req'd for HART <sup>®</sup> low resistance loops)
1W-9A820-1	Rechargeable Battery 9600mAh Li-Ion
1W-9P802	USB Cable - Communication from Docking Station to PC
1W-9P790	FieldMate Carrying Case - Custom soft case with integrated HART <sup>®</sup> lead compartment
1W-9P791	Hand Strap - Equipment protection equipment
1W-9P780	SD Card - Micro
1W-9P822	YHC5150X Series battery charger power cord (included w/ unit)
1W-9P823	7/64" Hex key wrench (included w/ unit). Fits the battery pack screws.

For more information, please visit us at [www.yokogawa.com/us](http://www.yokogawa.com/us)

### Trademarks

All brand or product names of Yokogawa Corporation of America in this document are trademarks or registered trademarks of Yokogawa Corporation of America. All other company brand or product names in this document are trademarks or registered trademarks of their respective holders.